



TITAN (Rocna) Grade 30, Grade 43 gekalibreerde gegalvaniseerde ankerketting DIN766 en ISO

Titan ketting : grade30, 43 hot dip gegalvaniseerd 100 micron zink

Maggi ketting: grade 70 hot dip gegalvaniseerd 60 micron zink

RVS ketting : Grade50 316L en 318LN (duplex)

TITAN Grade 30	Artikel nr.	D in mm	P in mm	specs	B in mm	gewicht kg/m	WLL kg	BLL kg
6mm	10325401	6	18,5	ISO4565	20	0,8	408	1632
8mm	10325152	8	24	ISO4565	26	1,4	816	3264
10mm DIN	10315915	10	28	DIN766	34	2,3	1275	5100
10mm ISO	10325145	10	30	ISO4565	34	2,3	1275	5100
12mm	10325147	12	36	ISO4565	40	3,3	1800	7300
13mm	10315918	13	36	DIN766	44	3,9	2040	8160
14mm	10315919	14	42	DIN766	46	4,4	2550	10200
16mm DIN	10315920	16	45	DIN766	54	6,1	3200	12800
TITAN Grade43	Artikel nr.	D in mm	P in mm	specs	B in mm	gewicht kg/m	WLL kg	BLL kg
6mm	10325555	6	18,5	DIN766	20	0,8	600	2400
8mm	10325557	8	24	DIN766	26	1,4	1100	4400
10mm DIN	10325558	10	28	DIN766	34	2,2	1800	7200
10mm ISO	10325559	10	30	ISO4565	34	2,2	1800	7200
12mm	10325560	12	36	DIN766	40	3,3	2400	9600
13mm	10325368	13	36	DIN766	44	3,9	3050	12200
14mm	10325561	14	42	DIN766	46	4,4	3250	13000
16mm	10325562	16	45	DIN766	54	6,1	4325	17300
Maggi AQUA Grade70	Artikel nr.	D in mm	P in mm	specs	B in mm	gewicht kg/m	WLL kg	BLL kg
AquaG70 8mm	AQUA7ZF080	8	24	DIN766	26	1,4	1400	7000
AquaG70 10mm	AQUA7ZF101	10	28 DIN	DIN766	34	2,2	2200	11000
AquaG70 10mm	AQUA7ZF100	10	30en813-3	DIN766	34	2,2	2200	11000
AquaG70 12mm	AQUA7ZF120	12	36	DIN766	40	3,3	3160	15800
AquaG70 13mm	AQUA7ZF130	13	36	DIN766	44	3,9	3700	18500
AquaG70 14mm	AQUA7ZF140	14	42	DIN766	46	4,4	4300	21500
AquaG70 16mm	AQUA7ZF161	16	45 DIN	DIN766	54	6,1	5600	28000
AquaG70 16mm	AQUA7ZF160	16	48en813-3	DIN766	54	6,1	5600	28000
EINDSCHALM	Artikel nr.	D in mm	P in mm	specs	B in mm	gewicht kg/m	WLL kg	BLL kg
8mm	GRIGR80080						1750	7000
10mm	GRIGR80100						2750	11000
13mm	GRIGR80130						4625	18500
RVS 316 grade 50 en 60	Artikel nr.	D in mm	P in mm	specs	B in mm	gewicht kg/m	WLL kg	BLL kg
RVS316l 8mm	316L8	8	24	DIN766	26	1,4	3000	6200
RVS316l 10mm	316L10	10	28	DIN766	34	2,3	3500	10000
RVS316l 10mm	316L11	10	30	ISO4564	34	2,3	3500	10000
RVS316l 12mm	316L12	12	36	ISO4564	40	3,8	7000	14000
RVS316l 13mm	316L13	13	36	DIN766	44	3,9	7000	14000
RVS318IN DUPLEX 8mm	318LN8	8	24	DIN766	26	1,4	3100	6500
RVS318IN DUPLEX 10mm	318LN10	10	28	DIN766	34	2,3	5100	10300

typefouten voorbehouden, rvs prijzen onderhevig aan markt ontwikkelingen,1-1-2019

n.b. ketting wordt geleverd inclusief fabriekscertificaat.

EOE , stainless steel prices subject to market changes,

p.s. chain shipped including manufactures certificated per 1-1-2019