

Non-Return Valves

TRUDESIGN[®] Non-Return Valves are designed for marine, farming, horticulture and mining industries. Made from UV stabilised glass reinforced Nylon, these composite material fittings are designed for the harsh marine and agricultural environments. They can be used in line to prevent water backflow or siphoning and have a very low cracking pressure.

Available in 5 sizes:



Key Features:

Feature:	Benefit:
Manufactured from a high strength, UV stabilised Glass Reinforced Nylon composite	High strength and lightweight. Can be used in direct sunlight
High impact and tensile strength	"Water hammer safe" and insensitive to pressure shocks in the pipeline
Stainless spring	No corrosion issues or risk of internal valve staying open
Low cracking pressure	Minimal pressure required to open the valve with minimal restriction on flow-rate
In line fitting	Minimal installation room needed and no other fittings required
Printed white arrow (opposite logo side)	Quick and easy identification of water flow direction

Part Numbers:

Model / Size	Part Number	Part Number PKG
Non-Return Valve ¾"	90804	90845
Non-Return Valve 1"	90805	90846
Non-Return Valve 1 ¼"	90806	90847
Non-Return Valve 1 ½"	90807	90848
Non-Return Valve 2"	90812	90849

Specifications:



Size:	¾" (19mm)	1" (25mm)	1 ¼" (32mm)	1 ½" (38mm)	2" (50mm)
Weight	21 g (0.7 oz)	34 g (1.2 oz)	50 g (1.8 oz)	67 g (2.4 oz)	119 g (4.2 oz)
Temp. Service	65°C	65°C	65°C	65°C	65°C
Temp. Max	93°C	93°C	93°C	93°C	93°C
Pressure Service	0 – 150 psi	0 – 150 psi	0 – 150 psi	0 – 150 psi	0 – 150 psi
Pressure Max	230 psi	230 psi	230 psi	230 psi	230 psi
Cracking Pressure	~ 0.41 psi	~ 0.29 psi	~ 0.26 psi	~ 0.23 psi	~ 0.22 psi
Recommended for flow-rates between *	15 – 42 Litre/min (4 – 11 gpm)	25 – 79 Litre/min (6.5 – 21 gpm)	32 – 117 Litre/min (8.5 – 31 gpm)	61 – 193 Litre/min (16 – 51 gpm)	87 – 322 Litre/min (23 – 85 gpm)
Pressure loss @ max flow-rate	3.8 psi (262 mbar)	3.8 psi (262 mbar)	2.8 psi (193 mbar)	2.3 psi (159 mbar)	2.9 psi (200 mbar)

* Choosing the right size valve for your application will reduce risks of wear, vibrations and noise. It is better to avoid using a valve either too small (leads to excessive velocity and wear) or too large (leads to vibration, noise and possibly premature wear of a non-return valve plunger that is never fully open).

Installation:

- Ensure the Non-Return Valve is installed with the water flowing in the same direction as the white arrow.
- Use 2 hose clamps on each end (4 total), ensuring not to over-tighten.
- Recommend use of a filter or strainer in flow path, feed side of the Non-Return Valve. Disconnect piping and check for blockages every 6 months.
- For clear water use only.

TruDesign Plastics Ltd. accepts no responsibility for products which are improperly installed or tampered with. Although the information presented in this product information sheet is believed to be accurate and reliable, no responsibility for inaccuracies can be assumed by TruDesign Plastics Ltd. This performance data is typical only and variations due to component manufacturing tolerances are normal. TruDesign Plastics Ltd. reserves the right at any time to change performance characteristics or specifications without prior notice.
TruDesign Plastics Ltd. 2016, all rights reserved.