

TECHNISCHE SPECIFICATIES				
T TYPE	SCHROEFAS DIAMETERS	BLAD DIA.	BREEDTE	MIN. TUSSENRUIMTE
SLIDE-ON	3/4" 7/8" 1" 1 1/8" 1 1/4" 20mm 22mm 25mm 28mm 30mm	3.15" 80mm	0.47" 12mm	0.7" 18mm
SLIDE-ON SPECIAL	1 1/4"	3.94" 100mm	0.47" 12mm	0.7" 18mm
SLIDE-ON	1 3/8" 1 1/2" 35mm 40mm	3.94" 100mm	0.47" 12mm	0.7" 18mm
SLIDE-ON	1 3/4" 2" 45mm 50mm	4.72" 120mm	0.47" 12mm	0.7" 18mm
CLAMP-ON STANDARD	3/4" 7/8" 1" 20mm 22mm 25mm	3.15" 80mm	0.67" 17mm	0.9" 23mm
CLAMP-ON STANDARD	1 1/8" 1 1/4" 30mm	3.35" 85mm	0.67" 17mm	0.9" 23mm
CLAMP-ON STANDARD	1 3/8" 1 1/2" 1 5/8" 35mm 40mm	3.74" 95mm	0.67" 17mm	0.9" 23mm
CLAMP-ON MEDIUM	1 3/4" 2" 45mm 50mm	4.13" 105mm	0.67" 17mm	0.9" 23mm
CLAMP-ON SPECIAL	1 3/4" 2" 45mm 50mm	5.00" 127mm	0.67" 17mm	0.9" 23mm
CLAMP-ON LARGE	2 1/4" 2 1/2" 55mm 60mm	4.57" 116mm	0.87" 22mm	1.26" 32mm
CLAMP-ON EXTRA LARGE	1 1/2" 1 3/4" 2" 2 1/4" 2 1/2" 45mm 50mm 55mm 60mm	6" 150mm	1.18" 30mm	1.65" 42mm
CLAMP-ON EXTRA LARGE	2 3/4" 3" 3 1/4" 3 3/8" 3 1/2" 4" 65mm 80mm 85mm 90mm 100mm	7.48" 190mm	1.3" 33mm	1.77" 45mm