

model	Afmetingen in inch en mm															
	A		B		C		D		E		F		G		H	
Type nr.	overall lengte		overall hoogte		min.gat maat lengte		min.gat maat hoogte		buiten radius		goot middelpunt		middelpunt naar goot		goot radius	
	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm	inch	mm
310B	13 1/4	336	5 3/8	137	11 1/8	283	3 1/4	83	R 2	51	5 3/4	146	1 1/2	38	R 7/8	22
317SS	20 1/4	514	6 3/4	172	18	458	4 1/8	105	R 2 1/8	54	11 1/8	283	2	51	R 1	25
410B/SS	13 1/4	336	7 1/4	185	11	280	5	127	R 2 3/8	60	4 3/4	121	2 3/8	60	R 7/8	22
414B/SS	17 3/8	442	7 3/8	188	15 1/8	385	5 1/8	130	R 2 3/8	60	7 7/8	200	2 7/8	73	R 1	25
512B/SS	15	381	8	204	12 3/4	324	5 3/4	146	R 2 1/4	57	6 3/4	172	2 3/4	70	R 7/8	22
512PW	15	381	8	204	12 5/8	321	5 5/8	143	R 2 1/4	57	5 1/8	130	2 7/8	73	R 5/8	16
515EL	210	462														eleptisch
620B	23 1/4	590	9 3/8	238	20 7/8	530	6 7/8	175	R 2 3/8	60	16 1/8	410	3 1/8	80	R 7/8	22
714B	17 1/8	435	10	254	14 3/4	375	7 3/4	197	R 2 3/8	60	8 3/4	222	3 5/8	92	R 7/8	22
715B/SS	18	458	10 1/8	257	15 3/4	400	7 3/4	197	R 2 3/8	60	8 3/4	222	3 3/4	95	R 1	25
715PW	18 1/4	465	10 1/4	260	15 3/4	400	7 3/4	197	R 2 1/2	64	11 1/4	286	4	102	R 3/4	19
726B/SS	29 5/8	753	10	254	27 1/4	693	7 3/4	197	R 2 3/8	60	20 1/4	514	3 3/4	95	R 1	25
818B/SS	21 1/4	540	11 3/8	290	18 5/8	474	8 5/8	219	R 2 1/2	64	11 7/8	302	4 1/4	108	R 7/8	22
822B/SS	27 1/8	690	11 3/8	290	23 5/8	600	8 5/8	219	R 2 1/2	64	14 7/8	378	4 1/4	108	R 7/8	22
5RB	8 1/4	210			5 7/8	150							2 7/8	73	R 7/8	22
6SS	9	229			6 5/8	169										
8RB/SS	10 1/4	260			8 5/8	219							4 1/4	108	R 7/8	22
8RPW	11 1/4	286			8 1/2	216							4 3/8	111	R 7/8	22
10SS	13	337			10,8	274										
12RSS	15 1/2	395			12 7/8	327							6 1/8	156	R 1	25

"B" brons patrijspoot "SS" rvs 316 patrijspoot "PW" TriMatrix patrijspoot  
 ----- rode lijn geeft de optimale gat maat aan

